

White Peak GC2



An impeccable, fully coated, hard sized folding boxboard with an uncoated cream reverse for a toothy feel. White Peak GC2 is an excellent choice for a wide variety of end uses and can be foiled, blocked, embossed and laminated.

This product is produced using ECF pulp from FSC® certified sources, ISEGA certified for direct food contact and is fully recyclable. ISO 9001 and ISO 14001 approved supplier.

Process suitability

White Peak GC2 is ideal for litho, gravure letterpress, flexo and screen printing. It's also suitable for UV and litho varnishing, emulsion coating, foil and film laminating, embossing and foil blocking. Not suitable for reverse printing.

Suggested uses

Point of sale displays • Cartons for cosmetics • Health care & pharmaceuticals • Food packaging • Frozen & chilled food packaging

Stock schedule

Thickness (mic)	370	410	435	470	505	540	610	690
Grammage (gsm)	210	225	235	255	270	290	320	355
450mm x 640mm	●	●	●	●	●	●	●	
520mm x 720mm	●	●	●	●	●	●	●	
600mm x 800mm				●	●		●	
640mm x 900mm		●	●	●	●	●	●	●
720mm x 1020mm	●	●	●	●	●	●	●	●
720mm x 950mm		●		●	●	●	●	
950mm x 720mm				●			●	
1020mm x 720mm		●	●		●		●	●

● Available from stock for next-day delivery

Specification

Thickness (mic)	370	410	435	470	505	540	610	690
Grammage (gsm)	210	225	235	255	270	290	320	355
Gloss (Hunter 75°) (%)	40	40	40	40	40	40	40	40
Stiffness (Taber 15°) (mNm)	MD	9.4	12.3	15.4	19.8	24.1	29.1	37.4
	CD	4.5	6	6.9	9.2	11.0	12.2	15.8

This information is given for general guidance only and is subject to change without notice.

Credentials



The CO₂ emissions from this product can be mitigated through the Carbon Capture® programme, directly supporting the work of the Woodland Trust.

This information is given for general guidance only and is subject to change without notice.